




BEARING DRIVESHAFT, INC.



NN3026KC1NAP4 Bearing 2D drawings and 3D CAD models

130 mm x 200 mm x 52 mm NTN
NN3026KC1NAP4 cylindrical roller bearings

Bearing No. NN3026KC1NAP4

Size	130x200x52 mm
Bore Diameter	130 mm
Outer Diameter	200 mm
Width	52 mm
d	130 mm
D	200 mm
B	52 mm
C	52 mm
Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	5.73
EAN	0692314627068
Product Group	B04270
Bore Profile	Tapered
Cage Material	Brass
Precision Class	ABEC 7 ISO P4
Number of Rows of Rollers	Double Row
Separable	Outer Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C1NA
Retainer	Yes



BEARING DRIVESHAFT, INC.

Relubricatable	Yes
Inch - Metric	Metric
Other Features	3 Rib Inner Ring Plain Outer Ring Precision Bearing Cage on Inner Ring OD
Long Description	130MM Bore; Tapered Bore Profile; 200MM Outside Diameter; 52MM Width; Brass Cage Material; ABEC 7 ISO P4; Double Row; Outer Ring - Both Sides Separable; No Snap Ring; Relubricatable; C1NA Internal
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	NN3026KC1NAP4
Weight / LBS	12.628
Bore	5.118 Inch 130 Millimeter
Width	2.047 Inch 52 Millimeter
Outside Diameter	7.874 Inch 200 Millimeter
bore diameter:	130 mm
maximum rpm:	3600 rpm
outside diameter:	200 mm
bearing material:	Hardened Alloy Steel
overall width:	52 mm
cage material:	High Strength, 2 piece, Machined Brass
flanges:	(3) Inner Ring
finish/coating:	Uncoated
bore type:	Tapered 1:12



BEARING DRIVESHAFT, INC.

closure type:	Open
number of rows:	2
resistance features:	Clean Room, Vacuum
internal clearance:	C1NA
outer ring width:	52 mm
operating temperature range:	-40 to 120 ° C
fillet radius:	2 mm
dynamic load capacity:	284000 N
series:	NN30K
static load capacity:	475000 N
manufacturer product page:	Click here
precision rating:	ISO Class 4