



BEARING DRIVESHAFT, INC.

55,5625 mm x 100 mm x 55,56 mm Timken
G1203KRRB deep groove ball bearings



G1203KRRB Bearing 2D drawings and 3D CAD models

Bearing No. G1203KRRB

| | |
|------------------------|---|
| Category | Insert Bearings Spherical OD |
| Inventory | 19.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 1.37 |
| Product Group | M06110 |
| Inner Race Profile | Wide Inner Ring |
| Outer Race Profile | Spherical |
| Relubricatable | Yes |
| Seal Type | Double Land Riding Rubber Contact |
| Mounting Method | Eccentric Collar |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Long Description | 2-3/16" Bore; Wide Inner Ring; Ball Bearing; 2-13/16" Length Thru Bore; 0.945" Outer Race Width; 3.937" Outside Diameter; Relubricatable; Double Land Riding Rubber Contact Seal; Ec |
| Inch - Metric | Inch |
| Other Features | Single Row Standard Duty |
| Category | Insert Bearings |
| UNSPSC | 31171536 |
| Harmonized Tariff Code | 8482.10.50.00 |
| | |



BEARING DRIVESHAFT, INC.

| Noun | Bearing |
|---------------------------------|---|
| Keyword String | Insert |
| Manufacturer URL | http://www.timken.com |
| Manufacturer Item Number | G1203KRRB AG |
| Weight / LBS | 3.01 |
| Outer Race Width | 0.945 Inch 24.003 Millimeter |
| d | 2.188 Inch 55.575 Millimeter |
| D | 2.813 Inch 71.45 Millimeter |
| D | 3.937 Inch 100 Millimeter |
| Shaft Size d | 2 3/16 in |
| Bore Type | Cylindrical bore |
| Bearing Type | Ball Bearing |
| Material | Bearing Steel |
| Lubrication Type | Relubricatable |
| O.D. Type | Spherical OD |
| Dimension M | 0.197 in |
| Dimension B2 | 0.811 in |
| Series | Industrial |
| Weight | 0.50 lb |
| Sub Series | G1...KRRB |
| Outside Diameter D | 3.937 in |
| Inner Ring Width B | 55.56 mm |
| Outside Ring Width C | 24.000 mm |
| Radius r | 0.6 mm |
| Center of Bearing from End S | 27.8 mm |
| Dimension S1 | 43.6 mm |
| Set Screw Size | 7/16-14 |
| Number of Set Screws | 2 |
| Angle between Set Screws | 90 ° |
| | |



BEARING DRIVESHAFT, INC.

| | |
|---------------------|-----------|
| Dimension B1 | 2.811 in |
| Static Load Rating | 6570 lbf |
| Dynamic Load Rating | 10800 lbf |